



ELBERT

DATE	
ITEM #	MT-ELBERT
PROJECT	
COMMENTS	
PREPARED BY	

DESCRIPTION

Double Drum Pendant Light

SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body.
Matte white acrylic bottom diffuser (Optional).

SHADES

Solid cold-rolled steel construction.
Material on heavy translucent white styrene with your choice of the coverings opacity.

FINISH

Standard: White (WHI)
Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available, but may impact extended lead time and standard price.

LIGHTING

5-way, standard socket cluster. Works with incandescent or LED bulbs.

INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

USAGE

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.
Pre-selected values may also be modified, if required.

ELBERT

S E R I E S

ELBERT: Double Drum
Pendant Light

3 0		3 0	8	2 4	2 4
<u>OUTER SHADE TOP DIAMETER</u>		<u>OUTER SHADE BOTTOM DIAMETER</u>	<u>OUTER SHADE HEIGHT</u>	<u>INNER SHADE TOP DIAMETER</u>	<u>INNER SHADE BOTTOM DIAMETER</u>
7		S R S			
<u>INNER SHADE HEIGHT</u>	<u>CANOPY TYPE</u>	<u>CANOPY COLOR</u>		<u>STEM COLOR</u>	
IN INCHES 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58, 60	SRS: Swivel Rigid Stem FC: Flex Cord AC: Aircraft Cable with Flex Cord	STANDARD WHI: White PREMIUM: NIC: Nickel BRA: Brass BLA: Black IVO: Ivory ORB: Oil-Rubbed Bronze		1/4" Round Steel STANDARD ST-WHI: White PREMIUM ST-NIC: Nickel ST-BRA: Brass ST-BLA: Black ST-IVO: Ivory ST-ORB: Oil-Rubbed Bronze	
			A		
<u>LAMP SHADE OPACITY</u>	<u>LAMP SHADE COVERING</u>	<u>ACRYLIC DIFFUSER</u>	<u>HEIGHT FROM CEILING TO SHADE BOTTOM</u>	<u>LAMPING</u>	
OPAQUE: Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade)	STANDARD (Some Examples) L-CRE: Linen Cream L-WHI: Linen White	A: With Acrylic Diffuser NA: Without Acrylic Diffuser	Specify the Length 6, 8, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, or CUSTOM	Specify Number of Light Sockets 1, 2, 3, 5	
TRANSLUCENT: Shade covering allows some light to shine through. Vertical bars are exposed.	PREMIUM (Some Examples) DL-OFF: Designer Linen Off-White VC-WHI: Vinyl Coated White		CUSTOM: Enter Actual Measurement in Inches		
VERTICAL TRIM: 1/2" trim applied to shade exterior over vertical support bars to hide shadows.				<u>B U L B S</u> Number of Bulbs Depends on Socket 9W2700: 800 Lumens 2,700K 15W2700: 1,600 Lumens 2,700K NA: No Bulbs	