



M A R C

DATE	
ITEM #	MT-MARC
PROJECT	
COMMENTS	
PREPARED BY	

DESCRIPTION

4-Tier Empire Pendant Light

SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body.
Matte white acrylic bottom diffuser
(Optional).

SHADES

Solid cold-rolled steel construction.
Material on heavy translucent white
styrene with your choice of the
coverings opacity.

FINISH

Standard: White (WHI)
Premium: Nickel (NIC), Brass (BRA),
Black (BLA), Ivory (IVO), Oil-Rubbed
Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with
a thickness of 0.118. Custom colors are
available, but may impact extended
lead time and standard price.

LIGHTING

5-way, standard socket cluster. Works
with incandescent or LED bulbs.

INSTALLATION

Easy-to-install universal swivel socket
to attach to standard 4" junction box.
120V power.

Cleaning Recommendation: Use a soft
cloth brush or a vacuum brush to dust
the outside of the lamp shade and a
clean soft white flannel cloth for the
inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire
Resistant or Stain Guard Fabric
coating.

USAGE

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with
their depth of experience, offer the
designer the flexibility to modify
standard luminaries for project-specific
solutions. Contact the factory
regarding scale options, unique
finishes, mounting, additional
materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.
Pre-selected values may also be modified, if required.

MARC

SERIES

MARC: 4-Tier Empire Pendant Light

24

5.75

FC

OUTER
SHADE
DIAMETER

IN INCHES

6, 8, 10, 12, 14, 16,
18, 20, 22, 24, 26,
28, 30, 32, 34, 36,
38, 40, 42, 44, 46,
48, 50, 52, 54, 56,
58, 60, 62, 64, 66,
68, 70, 72, 74, 76,
78, 80

OUTER
SHADE
HEIGHT

IN INCHES

6, 8, 10, 12, 14, 16,
18, 20, 22, 24, 26,
28, 30, 32, 34, 36,
38, 40, 42, 44, 46,
48, 50, 52, 54, 56,
58, 60

CANOPY
TYPE

SRS: Swivel Rigid Stem

FS: Fixed Stem

FC: Flex Cord

AC: Aircraft Cable with
Flex Cord

CANOPY
COLOR

STANDARD

WHI: White

PREMIUM

NIC: Nickel

BRA: Brass

BLA: Black

IVO: Ivory

ORB: Oil-Rubbed Bronze

CORD
COLOR

STANDARD

C-BLA: Black

C-WHI: White

A

1

CORD
LENGTH

IN FEET

4, 8, 12, 16

LAMP SHADE
OPACITY

OPAQUE:

Features an interior
light-blocking layer to
make shade opaque. (No
light passes through the
sides of the shade)

TRANSLUCENT:

Shade covering allows
some light to shine
through. Vertical bars
are exposed.

VERTICAL TRIM:

1/2" trim applied to
shade exterior over
vertical support bars to
hide shadows.

LAMP SHADE
COVERING

STANDARD

(Some Examples)

L-CRE: Linen Cream

L-WHI: Linen White

PREMIUM

(Some Examples)

DL-OFF: Designer Linen
Off-White

VC-WHI: Vinyl Coated
White

ACRYLIC
DIFFUSER

A: With Acrylic
Diffuser

FBD: With Fabric
Diffuser

NA: Without
Acrylic Diffuser

LAMPING

Specify Number of
Light Sockets

1, 2, 3, 5

BULBS

Number of Bulbs
Depends on Socket

9W2700:

800 Lumens 2,700K

15W2700:

1,600 Lumens 2,700K

NA: No Bulbs

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.
Pre-selected values may also be modified, if required.

MARC

S E R I E S

MARC: 4-Tier Empire Pendant Light

9	24	5.75	9.45	OUTER SHADE
<u>OUTER SHADE TOP DIAMETER</u>	<u>OUTER SHADE BOTTOM DIAMETER</u>	<u>OUTER SHADE HEIGHT</u>	<u>OUTER SHADE SLANT HEIGHT</u>	
16				
7	16	8.25	9.4	INNER SHADE 2
<u>INNER SHADE 2 TOP DIAMETER</u>	<u>INNER SHADE 2 BOTTOM DIAMETER</u>	<u>INNER SHADE 2 HEIGHT</u>	<u>INNER SHADE 2 SLANT HEIGHT</u>	
7	9	5.5	5.59	INNER SHADE 3
<u>INNER SHADE 3 TOP DIAMETER</u>	<u>INNER SHADE 3 BOTTOM DIAMETER</u>	<u>INNER SHADE 3 HEIGHT</u>	<u>INNER SHADE 3 SLANT HEIGHT</u>	
16				
4.5	4.5	7	7	INNER SHADE 4
<u>INNER SHADE 4 BOTTOM DIAMETER</u>	<u>INNER SHADE 4 BOTTOM DIAMETER</u>	<u>INNER SHADE 4 HEIGHT</u>	<u>INNER SHADE 4 SLANT HEIGHT</u>	