



## TANJA

DATE	
ITEM #	MT-TANJA
PROJECT	
COMMENTS	
PREPARED BY	

## DESCRIPTION

Round Drum Pendant Light

## SPECIFICATION FEATURES

### MATERIAL / MOUNTING

Cold-rolled steel frame wire body.  
Matte white acrylic bottom diffuser (Optional).

### SHADES

Solid cold-rolled steel construction.  
Material on heavy translucent white styrene with your choice of the coverings opacity.

### FINISH

Standard: White (WHI)  
Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed Bronze (ORB)

### ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available, but may impact extended lead time and standard price.

### LIGHTING

Single socket, works with incandescent or LED bulbs.

### INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

### OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

### USAGE

Approved for interior locations only.

### MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

## ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.  
Pre-selected values may also be modified, if required.

### TANJA

#### SERIES

TANJA: Round Drum  
Pendant Light

1 6

1 6

S R S

#### SHADE DIAMETER

IN INCHES

6, 8, 10, 12, 14, 16,  
18, 20, 22, 24, 26,  
28, 30, 32, 34, 36,  
38, 40, 42, 44, 46,  
48, 50, 52, 54, 56,  
58, 60

#### SHADE HEIGHT

IN INCHES

6, 8, 10, 12, 14, 16,  
18, 20, 22, 24, 26,  
28, 30, 32, 34, 36,  
38, 40, 42, 44, 46,  
48, 50, 52, 54, 56,  
58, 60

#### SUSPENSION STYLE

SRS: Swivel Rigid Stem

FS: Fixed Stem

FC: Flex Cord

AC: Aircraft Cable with  
Flex Cord

#### CANOPY COLOR

STANDARD

WHI: White

PREMIUM

NIC: Nickel

BRA: Brass

BLA: Black

IVO: Ivory

ORB: Oil-Rubbed Bronze

#### STEM COLOR

3/8" Round Steel

STANDARD

ST-WHI: White

PREMIUM

ST-NIC: Nickel

ST-BRA: Brass

ST-BLA: Black

ST-IVO: Ivory

ST-ORB: Oil-Rubbed  
Bronze

A

3

#### HEIGHT FROM CEILING TO SHADE BOTTOM

IN INCHES

Specify the Length

6, 8, 12, 14, 16, 18, 20,  
22, 24, 26, 28, 30, 32, 34,  
36, 38, 40, 42, 44, 46, 48,  
or CUSTOM

CUSTOM: Enter Actual  
Measurement in Inches

#### LAMP SHADE OPACITY

OPAQUE:

Features an interior  
light-blocking layer to  
make shade opaque. (No  
light passes through the  
sides of the shade)

TRANSLUCENT:

Shade covering allows  
some light to shine  
through.

#### LAMP SHADE COVERING

STANDARD  
(Some Examples)

L-CRE: Linen Cream

L-WHI: Linen White

PREMIUM  
(Some Examples)

DL-OFF: Designer Linen  
Off-White

VC-WHI: Vinyl Coated  
White

#### ACRYLIC DIFFUSER

A: With Acrylic  
Diffuser

FBD: With Fabric  
Diffuser

NA: Without  
Acrylic Diffuser

#### LAMPING

Specify Number of  
Light Sockets

1, 2, 3, 5

#### BULBS

Number of Bulbs  
Depends on Socket

9W2700:

800 Lumens 2,700K

15W2700:

1,600 Lumens 2,700K

NA: No Bulbs