

maratodd

L I G H T I N G

FIXTURE TYPE
ALVIN DRUM SWIVEL RIGID STEM
www.maratodd.com

ALVIN

DATE	
ITEM #	ALVIN Drum Pendant Light with Swivel Rigid Stem
PROJECT	
COMMENTS	
PREPARED BY	



DESCRIPTION

ALVIN Drum Pendant Light with Swivel Rigid Stem Suspension Style.

SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body. Matte white acrylic bottom diffuser (Optional).

SHADES

Solid cold-rolled steel construction. Material on heavy translucent white styrene with your choice of the covering's opacity.

FINISH

Standard: White (WHI)
Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available but may impact extended lead time and standard price.

LIGHTING

Standard socket available in multiple configurations. Works with incandescent or LED bulbs.

INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

USAGE

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.
Pre-selected values in black may also be modified, if required.

ALVIN DRUM SWIVEL RIGID STEM
<u>SERIES</u>
ALVIN Round Drum Pendant Light

54"	18"	SRS	5		
<u>TOP + BOTTOM DIAMETER</u>	<u>SHADE HEIGHT</u>	<u>SUSPENSION STYLE</u>	<u>SOCKET</u>	<u>BRIGHTNESS</u>	
Even numbers only in inches, minimum 6" with maximum of 84"	Even numbers only in inches, minimum 4" with maximum of 48"	SRS: Swivel Rigid Stem	Single	<u>9W</u> 800 Lumens	<u>15W</u> 1,600 Lumens
			Double	1,600 Lumens	3,200 Lumens
			Triple	2,400 Lumens	4,800 Lumens
			5-Bulb	4,000 Lumens	8,000 Lumens
				<u>COLOR TEMPERATURE</u>	
				2,700K - Warm White	
				3,000K – Soft White	
				A	
<u>DISTANCE FROM CEILING TO INNER SHADE BOTTOM</u>	<u>STEM COLOR</u>	<u>LAMPSHADE OPACITY</u>	<u>LAMPSHADE COVERING</u>	<u>ACRYLIC DIFFUSER</u>	
In inches, up to 192"	3/8" Round Steel				
	STANDARD	OPAQUE:	STANDARD	A: With Acrylic Diffuser	
	ST-WHI: White	Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade)	(Some Examples)	FBD: With Fabric Diffuser	
	PREMIUM		L-CRE: Linen Cream	NA: Without Acrylic Diffuser	
	ST-NIC: Nickel		L-WHI: Linen White		
	ST-BRA: Brass		PREMIUM	Note: Fixture Diameters of 40" + get Diffuser Risers and	
	ST-BLA: Black	TRANSLUCENT:	(Some Examples)	Finials	
	ST-IVO: Ivory	Shade covering allows some light to shine through.	DL-OFF: Designer		
	ST-ORB: Oil-Rubbed Bronze	Vertical bars are exposed.	Linen Off-White		
	<u>CANOPY COLOR</u>		VC-WHI: Vinyl Coated White		
	STANDARD	VERTICAL TRIM:			
	WHI: White	1/2" trim applied to shade exterior over vertical support bars to hide shadows.			
	PREMIUM				
	NIC: Nickel				
	BRA: Brass				
	BLA: Black				
	IVO: Ivory				
	ORB: Oil-Rubbed Bronze				