

maratodd

L I G H T I N G

FIXTURE TYPE
BASTIAN TAPERED
SWIVEL RIGID STEM
www.maratodd.com

CUSTOM

DATE	
ITEM #	MT-BASTIANTAPERED-SWIVEL-RIGID-STEM
PROJECT	
COMMENTS	
PREPARED BY	



DESCRIPTION

BASTIAN Round Tapered Pendant Light with Swivel Rigid Stem Suspension Style.

SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body. Matte white acrylic bottom diffuser (Optional).

SHADES

Solid cold-rolled steel construction. Material on heavy translucent white styrene with your choice of the covering's opacity.

FINISH

Standard: White (WHI)
Premium: Nickel (NIC), Brass (BRA),
Black (BLA), Ivory (IVO), Oil-Rubbed
Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available but may impact extended lead time and standard price.

LIGHTING

Standard socket available in multiple configurations. Works with incandescent or LED bulbs.

INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

USAGE

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.
Pre-selected values in black may also be modified, if required.

BASTIAN TAPERED SWIVEL RIGID STEM

SERIES

BASTIAN: Round Tapered Pendant Light

24	12	SRS	3		
<u>SHADE TOP DIAMETER</u>	<u>SHADE SLANT HEIGHT</u>	<u>SUSPENSION STYLE</u>	<u>SOCKET</u>	<u>BRIGHTNESS</u>	
Even numbers only in inches, minimum 6" with maximum of 84"	Even numbers only in inches, minimum 4" with maximum of 48"	SRS: Swivel Rigid Stem		<u>9W</u>	<u>15W</u>
			Single	800 Lumens	1,600 Lumens
			Double	1,600 Lumens	3,200 Lumens
			Triple	2,400 Lumens	4,800 Lumens
			5-Bulb	4,000 Lumens	8,000 Lumens
<u>SHADE BOTTOM DIAMETER</u>				<u>COLOR TEMPERATURE</u>	
Even numbers only in inches, minimum 6" with maximum of 84"				2,700K - Warm White	
				3,000K – Soft White	

				A
<u>DISTANCE FROM CEILING TO SHADE BOTTOM</u>	<u>STEM COLOR</u>	<u>LAMPSHADE OPACITY</u>	<u>LAMPSHADE COVERING</u>	<u>ACRYLIC DIFFUSER</u>
IN INCHES	STANDARD	OPAQUE:	STANDARD	A: With Acrylic Diffuser
Specify the Length	ST-WHI: White	Features an interior	(Some Examples)	FBD: With Fabric Diffuser
6, 8, 12, 14, 16, 18, 20,	PREMIUM	light-blocking layer to		NA: Without Acrylic Diffuser
22, 24, 26, 28, 30, 32,	ST-NIC: Nickel	make shade opaque.	L-CRE: Linen Cream	
34, 36, 38, 40, 42, 44,	ST-BRA: Brass	(No light passes	L-WHI: Linen White	
46, 48, or CUSTOM	ST-BLA: Black	through the sides of the	PREMIUM	Note: Fixture Diameters
	ST-IVO: Ivory	shade)	(Some Examples)	of 40"+ get Diffuser
CUSTOM: Enter	ST-ORB: Oil-Rubbed			Risers and Finials
Actual Measurement	Bronze	TRANSLUCENT:	DL-OFF: Designer	
in Inches		Shade covering allows	Linen Off-White	
	<u>CANOPY COLOR</u>	some light to shine	VC-WHI: Vinyl	
	STANDARD	through. Vertical bars	Coated White	
	WHI: White	are exposed.		
	PREMIUM	VERTICAL TRIM:		
	NIC: Nickel	1/2" trim applied to		
	BRA: Brass	shade exterior over		
	BLA: Black	vertical support bars to		
	IVO: Ivory	hide shadows.		
	ORB: Oil-Rubbed Bronze			