maratodd

FIXTURE TYPE

JUERGEN-RECTANGLE DOUBLE TIER SWIVEL RIGID STEM

www.maratodd.com

JUERGEN

DATE	
ITEM#	MT-JUERGEN-RECTANGLE-DOUBLE- TIER-SWIVEL RIGID STEM
PROJECT	
COMMENTS	
PREPARED BY	



DESCRIPTION

JUERGEN Rectangle Double Tier Pendant Light

SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body. Matte white acrylic bottom diffuser (Optional).

SHADES

Solid cold-rolled steel construction. Material on heavy translucent white styrene with your choice of the covering's opacity.

FINISH

Standard: White (WHI)

Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed

Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available but may impact extended lead time and standard price.

LIGHTING

Standard socket available in multiple configurations. Works with incandescent or LED bulbs.

INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

USAGE

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification. Pre-selected values in black may also be modified, if required.

CUSTOM SQUARE/RECTANGLE OR OVAL DOUBLE TIER SWIVEL RIGID STEM

SERIES

CUSTOM: Double Tier Square/Rectangle or Oval Pendant Light

70×22	10	SRS	5		
	OUTER SHADE SLANT HEIGHT	SUSPENSION STYLE	<u>SOCKET</u>	BRIGHTNESS	
68 x 18 INNER SHADE TOP DIMENSION	INNER SHADE EXPOSED HEIGHT Even numbers only in inches, minimum " with maximum of 48"	SRS: Swivel Rigid Stem	Single Double Triple 5-Bulb	2,700K – V	15W 1,600 Lumens 3,200 Lumens 4,800 Lumens 8,000 Lumens MPERATURE Warm White Soft White

				Α
DISTANCE FROM CEILING TO INNER SHADE BOTTOM In inches, up to 192" STEM COLOR 3/8" Round Steel STANDARD ST-WHI: White PREMIUM ST-NIC: Nickel ST-BRA: Brass ST-BLA: Black ST-IVO: Ivory ST-ORB: Oil-Rubbed Bronze	CANOPY COLOR STANDARD WHI: White PREMIUM NIC: Nickel BRA: Brass BLA: Black IVO: Ivory ORB: Oil-Rubbed Bronze	LAMPSHADE OPACITY OPAQUE: Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade) TRANSLUCENT: Shade covering allows some light to shine through. Vertical bars are exposed. VERTICAL TRIM: 1/2" trim applied to shade exterior over vertical support bars to	LAMPSHADE COVERING STANDARD (Some Examples) L-CRE: Linen Cream L-WHI: Linen White PREMIUM (Some Examples) DL-OFF: Designer Linen Off-White VC-WHI: Vinyl Coated White	ACRYLIC DIFFUSER A: With Acrylic Diffuser FBD: With Fabric Diffuser NA: Without Acrylic Diffuser Note: Fixture Diameters of 40"+ get Diffuser Risers and Finials
		hide shadows.		