maratodd

FIXTURE TYPE

JAN DRUM FLEX CORD

www.maratodd.com

JAN

DATE	
ITEM#	Drum Pendant Light with Flex Cord
PROJECT	
COMMENTS	
PREPARED BY	

HEIGHT FROM CEILING TO SHADE BOTTOM SHADE HEIGHT SHADE HEIGHT

DESCRIPTION

Drum Pendant Light with Flex Cord Suspension Style.

SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body. Matte white acrylic bottom diffuser (Optional).

SHADES

Solid cold-rolled steel construction. Material on heavy translucent white styrene with your choice of the covering's opacity.

FINISH

Standard: White (WHI)

Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed

Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available but may impact extended lead time and standard price.

LIGHTING

Standard socket available in multiple configurations. Works with incandescent or LED bulbs.

INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

USAGE

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification. Pre-selected values in black may also be modified, if required.

JAN DRUM FLEX CORD

SERIES

JAN Round Drum Pendant Light

36	8	FC	5			
TOP + BOTTOM DIAMETER Even numbers only in inches, minimum 6" with maximum of 84"	SHADE HEIGHT	SUSPENSION STYLE FC: Flex Cord	SOCKET Single Double Triple 5-Bulb	9W 800 Lumens 1,600 Lumens 2,400 Lumens 4,000 Lumens	15W 1,600 Lumens 3,200 Lumens 4,800 Lumens 8,000 Lumens	
					2,700K - Warm White 3,000K – Soft White	
				3,000K		
CORD LENGTH In inches, up to 192"	CORD COLOR 3/8" Round Steel STANDARD ST-WHI: White PREMIUM ST-NIC: Nickel ST-BRA: Brass ST-BLA: Black ST-IVO: Ivory ST-ORB: Oil-Rubbed Bronze CANOPY COLOR STANDARD WHI: White PREMIUM NIC: Nickel	DPACITY OPACITY OPACITY OPACITY OPACITY OPACITY Features an intellight-blocking late to make shade opaque. (No liappasses through sides of the shades of the shades of the shades covering allows some light shine through. Vertical bars are exposed. VERTICAL To 1/2" trim applies shade exterior of the shades of the shad	ENT: DL-OFF: Lance Of VC-WHI: CO' STA (Some of VC-WHI: White	Examples) Finen Cream Innen White EMIUM Examples) Designer F	A: With Acrylic Diffuser FBD: With Fabric Diffuser NA: Without Acrylic Diffuser Note: Fixture Diameters of 40" + get Diffuser Risers and Finials	
	NIC: Nickel BRA: Brass BLA: Black IVO: Ivory ORB: Oil-Rubbed Bron	shade exterior of vertical support to hide shadows	over bars			