maratodd

FIXTURE TYPE

DRUM SWIVEL RIGID STEM

www.maratodd.com

GERTRUD

DATE	
ITEM#	MT-GERTRUD
PROJECT	
_	
COMMENTS	
PREPARED BY	



DESCRIPTION

Round Drum Pendant Light with Swivel Rigid Stem Suspension Style.

SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body. Matte white acrylic bottom diffuser (Optional).

SHADES

Solid cold-rolled steel construction. Material on heavy translucent white styrene with your choice of the covering's opacity.

FINISH

Standard: White (WHI)

Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed

Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available but may impact extended lead time and standard price.

LIGHTING

Standard socket available in multiple configurations. Works with incandescent or LED bulbs.

INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

USAGE

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification. Pre-selected values in black may also be modified, if required.

GERTRUD DRUM SWIVEL RIGID STEM

 \underline{SERIES}

MT-GERTRUD Drum Pendant Light

36	12	SRS	3		
TOP + BOTTOM <u>DIAMETER</u>	SHADE HEIGHT	<u>SUSPENSION</u> <u>STYLE</u>		<u>BRIGHTNESS</u>	
Even numbers only in inches, minimum 6" with maximum of 84"	Even numbers only in inches, minimum 4" with maximum of 48"	SRS: Swivel Rigid Stem	SOCKET Single Double Triple 5-Bulb	9W 800 Lumens 1,600 Lumens 2,400 Lumens 4,000 Lumens	15W 1,600 Lumens 3,200 Lumens 4,800 Lumens 8,000 Lumens
				<u>COLOR TEM</u> 2,700K - W 3,000K - S	Varm White

				Α
<u>DISTANCE FROM</u> CEILING TO INNER	STEM COLOR	<u>LAMPSHADE</u> OPACITY	<u>LAMPSHADE</u> COVERING	<u>ACRYLIC</u> DIFFUSER
SHADE BOTTOM	3/8" Round Steel	<u>01710111</u>	<u>GOVERNIVO</u>	<u>DIFF COLIC</u>
In inches, up to 192"	STANDARD ST-WHI: White	OPAQUE:	STANDARD (Some Examples)	A: With Acrylic Diffuser
	PREMIUM to ST-NIC: Nickel op ST-BRA: Brass pa ST-BLA: Black sic ST-IVO: Ivory ST-ORB: Oil-Rubbed	Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade) TRANSLUCENT: Shade covering allows some light to shine through. Vertical bars are exposed. VERTICAL TRIM: 1/2" trim applied to shade exterior over vertical support bars to hide shadows.	L-CRE: Linen Cream L-WHI: Linen White PREMIUM (Some Examples) DL-OFF: Designer Linen Off-White VC-WHI: Vinyl Coated White	FBD: With Fabric Diffuser NA: Without Acrylic Diffuser Note: Fixture Diameters of 40" + get Diffuser Risers and Finials
CANOPY COLOR STANDARD WHI: White PREMIUM NIC: Nickel BRA: Brass BLA: Black IVO: Ivory ORB: Oil-Rubbed Bronz	STANDARD			
	PREMIUM NIC: Nickel BRA: Brass BLA: Black			