

155 West 3rd St • New Richmond, WI 54017
p: 715.246.2233 f: 715.246.2243
www.maratodd.com



PHILADELPHIA

DATE	
ITEM #	LS-PHILADELPHIA
PROJECT	
COMMENTS	
PREPARED BY	

DESCRIPTION

Lumashade Round Drum Pendant Light

SPECIFICATION FEATURES

CONSTRUCTION

1/4" steel wireframe, painted for optimum reflectivity.
Power source located on-board or remote in ceiling.
Cable mount suspension system (supplied).

LIGHT SOURCE

Proprietary epoxy encased light emitting diode round disc.
NO. LEDs AND LIGHT OUTPUT
8" Round Disc (87 LEDs) - 1,800 Max Lumens
16" Round Disc (192 LEDs) - 4,000 Max Lumens
24" (440 LEDs) and 32" (446) Round Disc - 9,000 Max Lumens

COLOR RENDERING INDEX

>75
MAXIMUM WATTAGE
8" Round Disc - 18.2W
16" Round Disc - 40W
24" and 32" Rounds Disc - 90W

ENVIRONMENT

Dry or Damp
AMBIENT TEMPERATURE

22°F - 122°F

CONTROLLER

MW UL Approved (>20W, >40W or >90W depending on LED disc selected).

CERTIFICATIONS

CE, RoHS, FCC, IP-67

INSTALLATION

Easy-to-install. Attaches to standard 4" junction box. 120V power.
Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

USAGE

Approved for interior locations only.

MODIFICATIONS

Lumashade's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **blue highlighted** areas for complete specification. Preselected values may also be modified, if required.

PHILADELPHIA

SERIES

PHILADELPHIA: Lumashade
Round Drum Pendant Light

4 8

1 6

A C

SHADE DIAMETER

IN INCHES

6, 8, 10, 12, 14, 16, 18, 20,
22, 24, 26, 28, 30, 32, 34,
36, 38, 40, 42, 44, 46, 48,
50, 52, 54, 56, 58, 60, 62

SHADE HEIGHT

IN INCHES

6, 8, 10, 12, 14, 16, 18, 20,
22, 24, 26, 28, 30, 32, 34,
36, 38, 40, 42, 44, 46, 48,
50, 52, 54, 56, 58, 60, 62

SUSPENSION STYLE

SRS: Swivel Rigid Stem

FS: Fixed Stem

FC: Flex Cord

AC: Aircraft Cable
with Flex Cord

CANOPY COLOR

STANDARD

WHI: White

PREMIUM:

NIC: Nickel

BRA: Brass

BLA: Black

IVO: Ivory

ORB: Oil-Rubbed Bronze

A

1 6

POWER CORD COLOR

STANDARD

C-BLA: Black

C-WHI: White

LAMPSHADE OPACITY

OPAQUE:

Features an interior
light-blocking layer to
make shade opaque.
(No light passes
through the sides of
the shade)

TRANSLUCENT:

Shade covering allows
some light to shine
through.

LAMPSHADE COVERING

STANDARD

(Some Examples)

L-CRE: Linen Cream

L-WHI: Linen White

PREMIUM

(Some Examples)

DL-OFF: Designer

Linen Off-White

VC-WHI: Vinyl

Coated White

ACRYLIC DIFFUSER

A: With Acrylic
Diffuser

NA: Without
Acrylic Diffuser

LUMA DISC SIZE

8: 8" Luma Disc

16: 16" Luma Disc

24: 24" Luma Disc

32: 32" Luma Disc

POWER CORD LENGTH

IN FEET

4, 8, 12, 16

DIMMING

N: No Dimming

0-10V: 0-10V
PWM Dimming

RC: Remote
Control Dimming

COLOR TEMPERATURE

3K: Warm White

4K: Neutral White