



## OLIVER

DATE	
ITEM #	MT-OLIVER
PROJECT	
COMMENTS	
PREPARED BY	

## DESCRIPTION

Round Drum Pendant Light

## SPECIFICATION FEATURES

### MATERIAL / MOUNTING

Cold-rolled steel frame wire body.  
Matte white acrylic bottom diffuser (Optional).

### SHADES

Solid cold-rolled steel construction.  
Material on heavy translucent white styrene with your choice of the coverings opacity.

### FINISH

Standard: White (WHI)  
Premium: Nickel (NIC), Brass (BRA),  
Black (BLA), Ivory (IVO), Oil-Rubbed  
Bronze (ORB)

### ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available, but may impact extended lead time and standard price.

### LIGHTING

5-way, standard socket cluster. Works with incandescent or LED bulbs.

### INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

### OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

### USAGE

Approved for interior locations only.

### MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

## ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.  
Pre-selected values may also be modified, if required.

OLIVER

S E R I E S

OLIVER: Round Drum  
Pendant Light

3 6

1 2

S R S

S H A D E  
D I A M E T E R

IN INCHES

6, 8, 10, 12, 14, 16,  
18, 20, 22, 24, 26,  
28, 30, 32, 34, 36,  
38, 40, 42, 44, 46,  
48, 50, 52, 54, 56,  
58, 60

S H A D E  
H E I G H T

IN INCHES

6, 8, 10, 12, 14, 16,  
18, 20, 22, 24, 26,  
28, 30, 32, 34, 36,  
38, 40, 42, 44, 46,  
48, 50, 52, 54, 56,  
58, 60

S U S P E N S I O N  
S T Y L E

**SRS:** Swivel Rigid Stem

**FS:** Fixed Stem

**FC:** Flex Cord

**AC:** Aircraft Cable with  
Flex Cord

C A N O P Y  
C O L O R

**STANDARD**

**WHI:** White

**PREMIUM**

**NIC:** Nickel

**BRA:** Brass

**BLA:** Black

**IVO:** Ivory

**ORB:** Oil-Rubbed Bronze

S T E M  
C O L O R

3/8" Round Steel

**STANDARD**

**ST-WHI:** White

**PREMIUM**

**ST-NIC:** Nickel

**ST-BRA:** Brass

**ST-BLA:** Black

**ST-IVO:** Ivory

**ST-ORB:** Oil-Rubbed  
Bronze

A

5

H E I G H T  
F R O M  
C E I L I N G  
T O S H A D E  
B O T T O M

IN INCHES

Specify the Length

6, 8, 12, 14, 16, 18, 20,  
22, 24, 26, 28, 30, 32, 34,  
36, 38, 40, 42, 44, 46, 48,  
or CUSTOM

CUSTOM: Enter Actual  
Measurement in Inches

L A M P S H A D E  
O P A C I T Y

**OPAQUE:**

Features an interior  
light-blocking layer to  
make shade opaque. (No  
light passes through the  
sides of the shade)

**TRANSLUCENT:**

Shade covering allows  
some light to shine  
through.

L A M P S H A D E  
C O V E R I N G

**STANDARD**

(Some Examples)

**L-CRE:** Linen Cream

**L-WHI:** Linen White

**PREMIUM**

(Some Examples)

**DL-OFF:** Designer Linen  
Off-White

**VC-WHI:** Vinyl Coated  
White

A C R Y L I C  
D I F F U S E R

**A:** With Acrylic  
Diffuser

**FBD:** With Fabric  
Diffuser

**NA:** Without  
Acrylic Diffuser

L A M P I N G

Specify Number of  
Light Sockets

1, 2, 3, 5

B U L B S

Number of Bulbs  
Depends on Socket

**9W2700:**

800 Lumens 2,700K

**15W2700:**

1,600 Lumens 2,700K

**NA:** No Bulbs